



**General**

The AIR960 Telescopic Under Floor Ventilator is designed to provide a clear airflow passage to the void underneath a suspended floor. The telescopic feature enables the AIR960 to adjust vertically between three and five brick courses although a AIR961 vertical extension is also available for multiples of two course adjustments as required. Use in conjunction with AIR920, AIR961, AIR9612, AIR1203, AIR1205, AIR1206.

**Details**

<b>REF</b>	AIR960	<b>MANUFACTURING PROCESS</b>	Injection moulded
<b>BOX SIZE (MM)</b>	465 X 880 X 290	<b>MATERIAL</b>	PPC - Polypropylene copolymer
<b>PALLET SIZE (M)</b>	1 X 1.2 X 2.25		
<b>FREE AREA</b>	78cm <sup>2</sup>		
<b>PACKING</b>	Product per box = 20, Boxes per pallet = 20	<b>COLOUR</b>	BLACK
<b>WEIGHT</b>	Product =435 g, Box = 9kg, pallet = 195kg		

**References**

**BRE: SIGES17/262**  
**BRE: FLOORS, FLOORING**  
**DOE: BUILDING REGS C4**  
**NHBC: STANDARDS 5.2**

Version 1.0

14/08/2018

DRN BY T.S.HUISH

DRG No. 007

**Airflow(Nicoll Ventilators) Limited, Unit 15 Queensway, Stem Lane Industrial Estate, New Milton, Hampshire, BH25 5NN**  
Telephone: 01425 611547 FAX:01425 638912 e-mail:sales@airflow-vent.co.uk

**Made in the UK**

Due to continuous development Airflow (Nicoll Ventilators) Limited reserves the right to amend the specification without notice.