



EXPOSED

CONCEALED

ALL UNITS
MEASURED
ARE IN
MILLIMETRES

General

The AIR950 dual purpose concealed/exposed weep vent is designed to meet N.H.B.C standards. The vent has a baffled grill and drip lip at each end which reduces the ingress of driving rain and wind. The grill size is specifically designed to be wide enough not to be blocked by water droplets, debris or paint. But still able to stop large insects from gaining access.

The AIR 950 dual purpose weep vent should be fitted in open perp joints and mortared into position. The weep vent should be spaced at no greater than 900mm centres. To meet N.H.B.C guidelines, it is recommended to site the weep holes at every 450mm (MAXIMUM) with at least 2 per opening above doors and windows.

Details

REF	AIR950	MANUFACTURING PROCESS	Injection moulded	
BOX SIZE (MM)	285 X 120 X 120	MATERIAL	PPC - Polypropylene copolymer For coloured PPH - Polypropylene homopolymer For Clear	
PALLET SIZE (M)	1 X 1.2 X 1.52			
FREE AREA	90mm ²			
PACKING	Product per box = 50, Boxes per pallet = 400			
WEIGHT	Product = 13g, Box = 0.83kg, Pallet = 360kg		COLOUR	White, Terracotta, Brown, Black, Buff, Light Grey, Clear

References

- BS5250
- BS5628
- BS8000
- NHBC:Standards6.1

Version 1.0	19/01/2016	DRN BY T.S.HUI SH	DRG No. AF-AIR950-005
Airflow(Nicol Ventilators) Limited, Unit 15 Queensway, Stem Lane Industrial Estate, New Milton, Hampshire, BH25 5NN Telephone: 01425 611547 FAX:01425 638912 e-mail:sales@airflow-vent.co.uk Made in the UK			
Due to continuous development Airflow (Nicol Ventilators) Limited reserves the right to amend the specification without notice.			