



ALL UNITS
MEASURED
ARE IN
MILLIMETRES

General

This rafter tray is simple to install, has an integrated insect screen which protects entry from large insects and birds. It is made from a lightweight and durable plastic. Suitable for closed and open rafters, new build and re-roofing applications. In use for rafters with 600mm centres and roof pitches for over 15°

To install, simply staple to nail to the rafters, ensuring the correct positioning to provide a ventilation channel above the insulation. There are directional arrows positioned on the tray that should be pointing down towards the eaves, in open rafter situations the trays should be fitted 30-35mm clear of the front of the brickwork to ensure adequate ventilation.

Details

REF	AIR9649	MANUFACTURING PROCESS	Vacuum formed
BOX SIZE (MM)	320 x 450 x 630	MATERIAL	R-PET
PALLET SIZE (M)	1 X 1.2 X 2		
FREE AREA	10,000mm ² per metre equivalent to a continuous gap of 10mm	ASSOCIATED PRODUCTS	AIR1300, AIR9648
PACKING	Product per box = 100, Boxes per pallet =20		
WEIGHT	Product = 100g, Box =12 kg, pallet = 255kg	COLOUR	BLACK

References

BS 5250: Control of condensation in buildings.
BS 9250: Design of the airtightness of ceilings in pitched roofs.
Approved Document L1 & L2: Conservation of fuel and power.
NHBC Technical Guidance 7.2: Pitched Roofs.
BRE Digest Report 262: Thermal Insulation: Avoiding Risks.
BRE Digest Report 270: Condensation in Insulated Domestic Roofs

Version 1.0	08/08/2018	DRN BY T.S.HUISH	DRG No. 009
-------------	------------	------------------	-------------

Airflow(Nicoll Ventilators) Limited, Unit 15 Queensway, Stem Lane Industrial Estate, New Milton, Hampshire, BH25 5NN
Telephone: 01425 611547 FAX:01425 638912 e-mail:sales@airflow-vent.co.uk
Made in the UK

Due to continuous development Airflow (Nicoll Ventilators) Limited reserves the right to amend the specification without notice.