

25mm 3 IN 1 EAVES PACK

REF: AIR1600



General

The 3 in one eaves vent pack provides a simple but effective solution to eaves ventilation by providing all the components necessary in one pack. Packs are available for continuous eaves ventilation of 25,000mm²/m. one whole pack consists of fascia vents, roll out rafter trays and underlay support trays for a 6m length of roof. This product is quick and easy to install, suitable for new build and re-roofing applications. Designed for 400mm,450mm and 600mm centres.

Fitting instructions

To install, nail the fascia vents directly onto the fascia board using 50mm x 3.35 nails, the roll out rafter is then rolled over the rafters to provide ventilation above the rafters, fix this to the rafters using clout nails or staples. The underlay support tray is then place over the top of the fascia vent and either nailed using clout nails or stapled through its top edge onto the rafters.

10mm EAVES PACKS AVAILIABLE

CODE	WIDTH OF ROLL OUT RAFTER TRAY	OVERFASCIA VENT	UNITS PER PALLET
AIR1600	6m x 300mm	25mm	50
AIR1604	6m x 400mm	25mm	50
AIR1606	6m x 600mm	25mm	50

Details

REF	AIR1600	MANUFACTURING PROCESS	Injection moulded, Vac formed
BOX SIZE (MM)	125 X 285 X 1025	MATERIAL	R-PET – roll panel, support tray
PALLET SIZE (M)	1 X 1.2 X 2.2		PPC – Over fascia vent
FREE AREA	25,000mm ² /m continuous eaves ventilation	ASSOCIATED PRODUCTS	AIR500, AIR1300, AIR1200, AIR1500, AIR2500
PACKING	Product per box = 1 X 6m ROLL PANNEL, 6 X 1m OVERFASCIA VENT, 10 X FELT SUPPORT TRAYS, Boxes per pallet = 60		
WEIGHT (AIR1500)	Product = N/A, Box = 3kg, Pallet = 195kg	COLOUR	BLACK

References

BRE: DIGEST 14/262/270 BSI: BS5250 BSI: BS5534 DOE: Building Regs F2 NHBC: Technical Bulletin 6/21 NHBC: Good Practice Guide NHBC: Standards 7.2 P.S.A: Defects in Buildings

Version 1.0

17/09/2018

DRN BY T.S.HUI SH

DRG No. 028